



BREATHER - TB



THREADED TYPE



TB - 35
TB - 65
TB - 165



TB - 05
TB - 25



MODEL	DISPLACEMENT	RATING	A	B	C	E	A / F	WT
		MICRON			STD IN BSPP			KGS
TB . 05 .	150 LPM	40						
			45	63	1/4"	8	25	0.13
TB . 05 . 10	90 LPM	10						
TB . 25 .	720 LPM	40						
			77	75	3/4"	10	30	0.25
TB . 25 . 10	400 LPM	10						
TB . 35 .	1000 LPM	10	110	138	1 - 1/2"	12	55	0.40
TB . 65 .	2000 LPM	10	145	145	2"	15	65	0.55
TB . 165 .	4000 LPM	10	185	195	2 - 1/2"	15	80	1.30

Note : TB 35 / 65 / 165 Nylon Housing


MODEL CODE : ASSEMBLY

TB	- 05	- 10	- * * *	- P	- *
SERIES	CAPACITY	FILTRATION	THREADS	FEATURE	FEATURE 3
	CFM	μ MICRONS	OPTIONAL #	SPECIAL #	OPTIONAL # (OMIT IF NOT REQD)
TB	05	40 - 40 μ Std	02* - 1/4" * B / N	P - PRESSURISED (5 P S I)	B - BLACK POWDER COATED CAP
			04S - 7/16" - 20 UNF	SG - SPLASH GUARD	
			03* - 3/8" * B / N	DS4 - DIP STICK 4"	
			06S - 9/16" - 18 UNF	DS6 - DIP STICK 6" (Ref - H3)	
			04* - 1/2" * B / N	DS8 - DIP STICK 8"	
			08S - 3/4" - 16 UNF		
	25	10 - 10 μ Nom	04* - 1/2" * B / N		Z - ZINC BLUE LACQUER COATED CAP
			08S - 3/4" - 16 UNF		
			06* - 3/4" * B / N		
			12S - 1-1/16" - 12 UNF		
			08* - 1" * B / N		
			16S - 1-5/16" - 12 UNF		
	35	10 - 10 μ Nom	10* - 1 - 1/4" * B / N		
			20S - 1-5/8" - 12 UNF		
			12* - 1 - 1/2" * B / N		
			24S - 1-7/8" - 12 UNF		
	65	10 - 10 μ Nom	16* - 2" * B / N		
			32S - 3" - 12 UNF		
	165	10 - 10 μ Nom	20* - 2-1/2" * B / N		
			40S - 3-1/2" - 12 UNF		

OPTIONAL / SPECIAL FEATURE (CONSULT FACTORY) - OMIT IF NOT REQUIRED

DIMENSIONS IN MM FOR REFERENCE ONLY

P - FEATURE



- BUILT IN VALVE ASSEMBLY HELPS TO MAINTAIN PRESET PRESSURE (5 P S I) IN THE TANK.
- ALLOWS FREE FLOW OF AIR INTO THE TANK IF PRESSURE FALLS BELOW ATMOSPHERIC.
- IF PRESSURE INSIDE TANK INCREASES VALVE RELEASES AT PRESET PRESSURE (5 P S I)
- DISPLACED AIR IS FILTERED & CLEAN

